mortar industry association

lortar news promoting quality factory-produced mortar

Producer members

C&G Concrete Ltd 01780 482000

CEMEX UK Materials Ltd 01932 568833

CPI Mortars Ltd 0845 850 9090

Hanson 0845 845 6699

Hugh King & Co 01294 557515

John Carr (Liverpool) Ltd 0151 2070067

Premier Mortars 0845 603 3406

RTU 02890851441

Remix Dry Mortar Ltd 01329 231200

Roadstone Dublin Ltd 00 35 31 4041200

Smiths Concrete Ltd 01295 278177

Tarmac Limited 08701 116116

Masonry construction reaches zero-carbon



Masonry construction can achieve a zero-carbon home

Government has recognised that masonry construction can achieve a zero-carbon home. Hidden away in the Spring Budget detail is confirmation that Code for Sustainable Homes level 5 – suitably met by good old brick, block and mortar - will be the highest level required when all new homes have to be zero carbon from 2016.

Head of architecture, housing and sustainability at the Concrete Centre, Guy Thompson, points out that tucked away in an appendix to the budget, government has announced that unregulated carbon

emissions produced by cooking and electrical appliances such as televisions are to be excluded from the definition. These account for between one third and half of a home's total emissions, with the rest coming from lighting, heating and hot water production.

Under original government plans house builders would have been required to fund renewable energy projects to offset emissions from household appliances, substantially increasing the price of new homes at a time when the house building industry can ill afford it.

* Further information on building to Code level 5 is available in the Concrete Centre publication 'Achieving Code level 5 in Concrete and Masonry' downloadable from http://www.concretecentre.com/online_ services/publication_library/publication_ details.aspx?PublicationId=695. Please note this is currently under review to reflect the changes in Part Loutlined in a further publication, Thermal Performance: Part L1A.

40 years of the MIA lunch

The MIA lunch celebrates its fortieth year in 2011.

Several venues around the country have been used for the prestigious industry event which has drawn up to 200 guests for an event over its history.

In more recent years the favourite venue has been the Royal Overseas League in London again the venue for 2011.

New MIA chairman appointed

Chief executive of CPI Mortars, Larry Dale, has become chairman of the Mortar Industry Association.



Larry has wide experience in the concrete and mortar industries having begun his career in the Tarmac technical department in 1983. He was subsequently given a post

in sales in the company's mortar business and progressed to southern region manager. In 1998, he joined CPI Mortars as a sales representative, four months after the company had set up the first dry mortar plant in the UK at Northfleet, Kent.

On becoming MIA chairman, Larry said: 'The Construction Industry and its suppliers have been under severe pressure in the last few years. There are small signs of improvement in certain sectors but no doubt we still have some tough times ahead. It is important during this time that the focus of the industry as a whole remains on delivering quality through its products, services, and its many skilled people.'



CEMEX mortars and screeds for Rowley College

CEMEX also supplied to Mec Serv Limited

over 800t of 1-4 sand-cement

CEMEX has recently finished supplying both mortars and screed to a new college being built by Interserve at Rowley Regis, Birmingham.



Screeds ideal answer for floor construction



Laying a cementitious floor screed

Benefits of factory-produced cementitious floor screeds are being restated by the MIA as part of its overall promotion of quality products available from its membership.

The screeds are high-quality products designed for all traditional screed applications including monolithic, bonded and unbonded construction.

A cementitious levelling screed, typically made from a 1:3 or 1:4.5 ratio of cement to sharp sand, is used to achieve a durable, flat surface ready to accept the final flooring finish. It may be applied onto either a solid in-situ concrete ground floor slab or onto a precast concrete floor unit.

Screeds are made under tightly-controlled factory conditions and delivered to site, ready to use. They have guaranteed mix proportions and overcome any potential problems relating to site mixing.

Benefits include:

- accurate cement content
- consistent strength
- reduced mixing and labour costs
- ${\color{red}\boldsymbol{\cdot}}\ reduced\ was tage\ and\ pilferage$
- guaranteed meeting of specification
- technical advice and test data available upon request.

Screeds can be left as laid or floated to produce a smooth surface on which to lay a specified flooring or finish. They can also be used to embed underfloor heating or to encompass ducting for other services. Reinforcement can be added as required, generally through use of a fine metal mesh or the addition of polypropylene fibres. Screeds can also be used in conjunction with insulation materials.

Self-levelling, flowing screeds are available.

Generally based on a calcium sulfate binder, these can provide significant additional benefits, including:

- speed of application
- finer surface finish
- · accuracy of placement and finishing,
- reduced thickness
- a substantial reduction in the number of movement joints required.



essential materials sustainable solutions

mortar industry association

Gillingham House 38–44 Gillingham Street London, SW1V 1HU

Tel +44 (0)20.7963 8000 Fax +44 (0)20.7963 8001 info@mineralproducts.org www.mortar.org.uk

MIA is part of the Mineral Products Association, the trade association for the aggregates, asphalt, cement, concrete, lime, mortar and sillica sand industries